

Odor-free Matt Emulsion

Product code: PW3108

Composition and Application Field

EVI Europe Emulsion is a high quality acrylic co-polymer latex paint pigmented with titanium dioxide and other light fast alkali resistant pigments. The product is virtually odor free when dried making it a more user friendly material than ordinary emulsion paints. It has a very good wash ability scrub resistance and good color retention property with a smooth and pleasing effect. It has excellent brush ability with good resistance to algae and fungal attacks. **[This product is certified by Dubai Central Laboratory following DM-DLCD-RD-DP21-2180-(IC) Specific Rules for Low Emitting Materials as per the 2017 Al Sa'fat Dubai Green Building Evaluation System.]**

Substrates: Concrete, cement plaster, masonry, gypsum, block work etc.

Area of Use: Interiors preferably.

Specification

Finish	: Smooth & Matt
Color	: White + all shades as per EVI shade card and custom made
Specific gravity	: 1.70 ± 0.02
Solids (% by volume)	: 45 ± 2
Diluent	: Sweet Water
Flash point	: Not Applicable
Spread Rate:	
While the spread rate is directly dependent on the surface profile and also the type of undulations it has, by roller and also the equipment they used, EVI Europe Emulsion it would cover app 11 m ² / liter at 40 microns per coat.	
Drying Time (30°C)	: Set to touch: 1 – 2 hours.
	: Ready for Recoat: app 2 - 3 hours.
Recommended DFT	: 2 coats. App 30 – 40 mic per coat.

Surface Preparation

A good surface preparation and following the method statement / recommended system procedure of EVI is an ideal recommendation for the application of EVI Europe Emulsion.

For Plaster, Masonry & Concrete

Achieve a good and clean surface by removing all contaminants and loose particles by cleaning & drying. A laitance free surface should be achieved by good sweep blast or a wire brush. Water washing under pressure is recommended. Apply the EVI PVA Primer, or EVI Acrylic Alkali resistant primer or EVI All Weather Tex primer and allow drying as per the data sheet and subject to one more coat for even coverage. For Exterior: Apply EVI filler compound (fine or coarse) evenly and allow drying and following it up with EVI Europe Emulsion for one or two coats. For Interior: After applying the EVI AR primer, apply a uniform layer of EVI Stucco putty and then follow it up with EVI Europe Emulsion for two coats.

Application Method

Adequate ventilation is an ideal situation as it helps in drying and the good application itself.

Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point.

- 1. Dilution:** One can add 5 to 10% of sweet water for ease of application depending on the suitability of application.
- 2. Brush:** It is in ideal recommendation especially to avoid runs and sags due to excess.
- 3. Roller:** Apply an even coat spreading uniformly taking care to avoid runs.

Paint System

EVI EUROPE EMULSION

- EVI Alkali Resistant Primer	
Or PVA Primer	1 coat
- EVI Stucco Putty	2 coats
- EVI Europe Emulsion	2 coats

* Recommended system to be applied as per surface preparation (suitable emulsion grades), or as per EVI technical advice

Storage and Shelf Life

Under dry and cool condition, storage stability can be sound up to 18 months in original sealed containers.

Handling

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Safety Precaution

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapor or spray. MSDS is available on request for the safe handling of this product.

First Aid

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention