Nova Vernici

PVA PRIMER SEALER ALKALI RESISTANT

Technical Data Sheet

Product code: PW1005

Composition and Application Field

NOVA PVA Primer Sealer Alkali Resistant is a copolymer based primer to penetrate into bare surfaces like masonry, plaster, brick work and other bare constructed structures. It has excellent adhesion to cement surfaces forming an ideal surface for subsequent layers of coatings. [This product is certified by Dubai Central Laboratory following DM-DLCD-RD-DP21-2180-(IC) Specific Rules for Low Emitting Materials as per the 2017 Al Sa'fat Dubai Green Building Evaluation System.]

Use

Substrates: Concrete, plaster, masonry, gypsum. Area of Use: Interiors / Exterior.

Specification

Finish Colour Specific gravity Solids (% by volume) Diluent Flash point Spread Rate: : Smooth : White : 1.43 ± .02 : 37 ± 1% : Sweet Water : Not Applicable

While the spread rate is directly dependent on the surface profile and also the type of undulations, over spray and also the equipment used, NOVA PVA Primer Sealer Alkali Resistant would cover app 12-18 m² / liter @ 30 microns.

Drying Time (30° C) Recommended DFT : Set to touch: 1 – 2 hours. : Ready for Recoat: app 3 – 4 hours :1 to 2 coats. App 20 – 30 mic per coat.

Surface Preparation

A good surface preparation and following the method statement / recommended system procedure of NOVA is an ideal recommendation for the application of NOVA PVA Primer Sealer Alkali Resistant.

For Plaster, Masonry & Concrete:

Achieve a good and clean surface by removing all contaminants and loose particles by cleaning & drying. A laitance free surface should be achieved by good sweep blast or a wire brush. Water washing under pressure is recommended. Apply the NOVA PVA Primer Sealer Alkali Resistant and allow drying as per the data sheet and subject to one more coat for sufficient coverage.

For old and painted surfaces:

In case of surfaces which are painted / or aged and if there is visible dusting, chalking or even friable, ensure that all the loose material is removed by scrapping or metal brush. Apply a good coat of NOVA Fungicidal wash compound and allow drying. Follow this by a regular coat or two of NOVA PVA Primer Sealer Alkali Resistant.

Application Method

Adequate ventilation is mandatory as it helps in drying and the good application itself. Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point.

One can add 5 to 10% of sweet water for ease of application depending on the suitability of application.

1. Brush: It is an ideal recommendation especially to avoid runs and sags due to excess material.

2. Roller: Apply an even coat spreading uniformly taking care to avoid runs.

Paint System

NOVA PVA Primer Sealer	NOVA PVA Primer Sealer	1 coat
Alkali Resistant	Alkali Resistant	
Recommended system to	NOVA Stucco Putty	2 coats
be applied as per surface preparation.	NOVA Gold Emulsions	2 coats

• Or as per NOVA technical advice

Storage and Shelf Life

Under dry and cool condition, storage stability can be sound up to 18 months in original sealed containers.

HANDLING

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Flash Point: Not applicable

Safety Precaution

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. MSDS is available on request for the safe handling of this product.

First Aid

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved industrial cleaner. Do not use solvent or thinners.

Inhalation: Move to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion, Do not induce vomiting. Obtain immediate medical attention.

The above Data Sheet is based on our experience and extensive laboratory tests. We guarantee only the quality of the product in this Data Sheet. For safety measurements and details refer to the Safety Data Sheet. Nova reserves the right to modify the contents of the Data Sheet at any time and without prior notice as a system requirement in updating the product.

This Technical Data Sheet surpasses all prNovaously issued versions.