

ACRYLIC MEDIUM TEXTURE

Product code: PW3802

Composition and Application Field

NOVA Acrylic Medium Texture is very tough coating based on special acrylate copolymer latex, pigmented with titanium dioxide and other alkali resistant pigments with good light fastness and also good water resistance. It forms a good aggregate with a selected range of mineral quartz and other texture inducing combinations of rock. Its formulation incorporates fungicides and algacides, and its build ensures outstanding weather resistance.

Use

Substrates: Concrete, plaster, masonry, gypsum, block work and timber

Area of Use: Interiors & exterior with a textured finish.

Specification

Finish	: Large Texture and Matt (with marble chips)
Color	: White + limited colors as required
Specific gravity	: 1.16 ± 0.02
Solids (% by volume)	: 55 ± 1
Diluent	: Sweet Water
Flash point	: Not Applicable
Spread Rate:	
While the spread rate is directly dependent on the surface profile and also the type of undulations it has, as a thumb ruler NOVA Acrylic Medium Texture would cover 1 - 2 sq. meters per liter. Drying Time (30° C) : Set to touch: 3 - 4 hours.	
Ready for Recoat: app 6 - 8 hours.	
Recommended DFT : 1 to 2 coats. App 300 - 600 mic per coat. (largely depends on surface)	

Surface Preparation

A good surface preparation and following the method statement / recommended system procedure of NOVA is an ideal recommendation for the application of **NOVA Acrylic Medium Texture For Plaster, Masonry & Concrete:**

Achieve a good and clean surface by removing all contaminants by cleaning & drying. A laitance free surface should be achieved by good sweep blast or a wire brush. Before applying the NOVA Acrylic Medium Texture apply one coat of NOVA Alkali Resistant Primer or NOVA All Weather Tex Primer and allow drying. Apply one good coat with a heavy roller and spread the same evenly to the desired texture. **For Old and Painted surfaces:**

In case of surfaces which are painted / or aged and if there is visible dusting, chalking or even friable, ensure that all the loose material is removed by scrapping or metal brush. If the situation is critical it is recommended to do torching of the same and apply a good coat of NOVA Fungicidal wash compound and allow drying. Follow this by a regular coat or two of NOVA alkali resistant primer and continue as in the above case with the full system.

For Wood & Timber:

Achieve a good and clean surface by removing all contaminants by

cleaning & drying treatment with NOVA Wood Preservative is advisable. Start of with a good coat of NOVA Wood Primer and allow to dry well and allow to dry well and continue as in the above case with the full system. Exclusions for successful application include perpetually wet surfaces and also large cavities on wood, concrete surfaces.

Application Method

Adequate ventilation is an ideal situation as it helps in drying and the good application itself. Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point. One can add 5 to 10% of sweet water for ease of application depending on the suitability of application. Application is done with appropriate roller to give the desired texture.

Caution:

a. Over diluting would result in a flat and wrong texture.

b. In case of hot climatic conditions where the substrate could be very hot it is necessary that adequate cooling is done after the primer is applied and before the application of the texture with good amounts of cold water.

Paint System

NOVA ACRYLIC MEDIUM TEXTURE	
-NOVA All Weather Tex Primer	1 coat
-NOVA Acrylic Medium Texture	2 coats

Storage & Shelf Life

Under dry and cool condition, storage stability can be sound up to 18 months in original sealed containers.

HANDLING

Disposal: As per the guidance and legislations of the local authority e.g. by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Flash Point: Not applicable

Safety Precaution

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Other industrial practices are applicable. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.

MSDS is available on request for the safe handling of this product.

FIRST AID

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.